

8000T All-Temp



Available
from stock
on ZipShip

Media Type	Label	✓	Adhesive Type	Permanent	✓
	Receipt			Removable	
	Tag			No Adhesive	
	Wristband		Environment	Indoor	✓
Material Type	Paper	✓		Outdoor	
	Synthetic		Properties	Cold Temperature	✓
Printing Technology	Direct Thermal (no Ribbon Required)			Deep Freeze	✓
	Thermal Transfer (Ribbon Required)	✓		High Temperature	
Finish	Matte	✓		Ultra High Temperature	
	Gloss			High Tack	
				Chemical Resistance	-

Additional Features

- Special adhesive is resistant to a wide temperature range, both at application and throughout the life of the label
- Produces excellent quality images especially rotated barcodes, graphics and small character even at higher print speeds
- Adhesive offers strength and excellent adhesion to a wide variety of surfaces
- BPA free
- Latex free adhesive

Suggested Applications

- Labelling of packaging material
- Compliance labelling
- Work in progress; especially in applications of varying temperatures
- Product identification
- Warehouse labelling especially where long-term storage and varying temperatures apply
- Cold storage labelling

Technical Specifications

	Description	Caliper
Facestock	Ultra smooth white topcoated paper	74 microns
Adhesive	Permanent acrylic adhesive	18 microns
Liner	Semi-bleached kraft liner	64 microns
Total		156 microns ±10%



Recommended Zebra Printers:	P4T™, desktop, mid-range and high-performance printers
Recommended Zebra Ribbons:	2300, 2100, 3400, 3200
Minimum Application Temperature: When the label is applied, the environment and surface should be above this temperature	-29°C
Service Temperature Range: Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range	-54°C to 93°C
Recommended Storage Conditions: Storage of product before use	1 year duration when stored at 22°C at 50% RH
Expected Life Span in Application: Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated	Indoor use, 1 year+

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order sample roll SAMPLE5024.