

### **ZEBRA**

# PolyPro 3000T Gloss


#### **FEATURES**

- Thermal transfer, gloss polypropylene label with a permanent acrylic adhesive
- Excellent smear/scratch resistance
- · Excellent chemical resistance
- · This material is suitable for fanfolding
- Meets FDA 175.105 for indirect food contact requirements
- Available in white (10026042RM)

#### **MATERIAL CONSTRUCTION**

Component	Description	Caliper
Facestock	Gloss white polypropylene film	2.6 mil
Adhesive	Permanent, acrylic- based	0.7 mil
Liner	40 lb. semi-bleached, kraft stock	2.2 mil
	TOTAL ± 10%	5.5 mil

#### ADHESIVE STRENGTH



#### **TEMPERATURE PERFORMANCE**

Minimum Application Temperature	Service Temperature	Optimal Storage Conditions
23° F (-5° C)	-20° F to 212° F (-29° C to 100° C)	72° F (22° C) at 50% RH

#### **EXPECTED EXTERIOR LIFE**

Up to 1 year

#### **CHEMICAL RESISTANCE**

		Suggested Ribbon	
	Chemical	6200	
	Blood	•	
J	Body Fluid	•	
Weak	Salt Water	•	
_	Water	•	
	Window Cleaner	•	
_	Alcohol	•	
Moderate	Ammonia	•	
Mod	Bleach	•	
	IPA	•	
_	Gasoline	•	
Harsh	Grease	•	
_	Oil	•	
	Acetone	•	
<b>9</b>	IR Reflow		
Extreme	MEK	•	
ú	TCE	•	
	Xylene	•	

#### ■ Recommended ■ Test in Your Application NR Not Recommended

## SUGGESTED APPLICATIONS

 Chemical drum labeling



· Test tube labeling



Indirect food labeling



Product identification



 Labeling packages in cold storage



All products should be pre-tested to ensure it meets all intended requirements of specific end-use applications.

#### For more information, visit www.zebra.com/supplies

Product Performance and Suitability: The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

NA and Corporate Headquarters | +1 800 423 0442 | inquiry4@zebra.com